

# BRAZED PLATE HEAT EXCHANGER | MODEL ABD055 DOUBLE WALL | SUBMITTAL

File no: 113.58

Date: MARCH 16, 2020

Supersedes: 113.58

Date: MARCH 26, 2018

| Job:        |         | Representative: | Representative: |       |  |  |
|-------------|---------|-----------------|-----------------|-------|--|--|
|             |         | Order No:       |                 | Date: |  |  |
| Engineer:   |         | Submitted by:   | Submitted by:   |       |  |  |
| Contractor: |         | Approved by:    | Approved by:    |       |  |  |
| QUANTITY    | TAG NO. | MODEL NO.       | COMMENTS        |       |  |  |
|             |         |                 |                 |       |  |  |
|             |         |                 |                 |       |  |  |
|             |         |                 |                 |       |  |  |

# ABD - BRAZED PLATE HEAT EXCHANGERS DOUBLE WALL

Armstrong's ABD brazed plate heat exchangers are designed to facilitate heat transfer between two media of different temperatures. ABD produces high heat transfer rates that allow for a compact, corrosion resistant and robust design.

## **DESCRIPTION**

| Number of plates (N): |                  |  |  |
|-----------------------|------------------|--|--|
| Design Pressure       | 363 psi (25 bar) |  |  |
| Max Temperature       | 385°F /196°C     |  |  |
| Plate Material        | 316 ss           |  |  |
| Braze Material        | Copper           |  |  |
| Connection Material   | 316 ss           |  |  |

#### TYPICAL SPECIFICATION

Furnish and install on the plans and described herein, an Armstrong ABDO55-\_\_\_\_\_\_ brazed plate heat exchanger. Each heat exchanger must be designed to have the capacity and pressure/temperature rating as detailed in the schedule. The heat exchanger must utilize 316L stainless steel plates and copper braze to separate the two fluids while transferring heat and preventing corrosion.

To prevent cross contamination of the two media the heat exchanger shall be of double wall design. The media shall be separated by two plates with an air gap between them providing a positive leak path with detection grooves.

Each heat exchanger shall be Armstrong ABD055-\_\_\_\_\_or approved equal.


# CONNECTIONS


|                | Size - inch | Location | Rating |
|----------------|-------------|----------|--------|
| Fluid 1 Inlet  | 1.00        | A2       | NPT    |
| Fluid 1 Outlet | 1.00        | A1       | NPT    |
| Fluid 2 Inlet  | 1.00        | B1       | NPT    |
| Fluid 2 Outlet | 1.00        | B2       | NPT    |

2

# **DIMENSIONS**

| DIMENSIONS in inch (mm) |       |       |       | VOLUME | WEIGHT |                |                    |                       |
|-------------------------|-------|-------|-------|--------|--------|----------------|--------------------|-----------------------|
|                         | Α     | В     | С     | D      | E      | L              | gals(ltrs)         | lbs(kgs)              |
|                         | 13.07 | 11.06 | 4.88  | 2.88   | 0.79   | 0.51 + 0.095N  | (0.01 × N) gals    | 4.0 + (0.3 × N) lbs   |
|                         | (332) | (281) | (124) | (73)   | (20)   | (12.95 + 2.4N) | (0.055 × N) liters | 1.5 + (0.135 × N) kgs |





#### TORONTO

+1 416 755 2291

# BUFFALO

+1 716 693 8813

#### BIRMINGHAM

+44 (0) 8444 145 145

#### MANCHESTER

+44 (0) 8444 145 145

# BANGALORE

+91 (0) 80 4906 3555

# SHANGHAI

+86 (0) 21 5237 0909

#### SÃO PAULO

+55 11 4785 1330

# LYON

+33 (0) 420 102 625

# DUBAI

+971 4 887 6775

#### MANNHEIM